

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/837,517	04/19/2001	Nobuo Suzuki	107317-00028	8208
7590 12/15/2004 ARENT FOX KINTNER PLOTKIN & KAHN, PLLC			EXAMINER	
			DANIELS, ANTHONY J	
Suite 600 1050 Connectic	eut Avenue N.W.		ART UNIT	PAPER NUMBER
Washington, DC 20036-5339			2615	
			DATE MAILED: 12/15/2004	

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)				
	09/837,517	SUZUKI ET AL.				
Office Action Summary	Examiner	Art Unit				
	Anthony J. Daniels	2615				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).						
Status						
1) Responsive to communication(s) filed on	·					
2a) This action is FINAL . 2b) ☑ Thi	s action is non-final.					
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) 1-20 is/are pending in the application.						
4a) Of the above claim(s) is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.	5) Claim(s) is/are allowed.					
6)⊠ Claim(s) <u>1-6,9,12-14,17 and 18</u> is/are rejected	6)⊠ Claim(s) <u>1-6,9,12-14,17 and 18</u> is/are rejected.					
7) Claim(s) <u>7,8,10,11,15,16,19 and 20</u> is/are obj	7)⊠ Claim(s) <u>7,8,10,11,15,16,19 and 20</u> is/are objected to.					
8) Claim(s) are subject to restriction and/	or election requirement.					
Application Papers						
9)⊠ The specification is objected to by the Examiner.						
10)⊠ The drawing(s) filed on <u>19 April 2001</u> is/are: a) accepted or b)⊠ objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12)⊠ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).						
a) ☑ All b) ☐ Some * c) ☐ None of:						
1. Certified copies of the priority documents have been received.						
2. Certified copies of the priority documents have been received in Application No						
3. Copies of the certified copies of the priority documents have been received in this National Stage						
application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.						
oss the attached detailed office action for a list of the certified copies flot received.						
Attachment(s)						
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948)		mmary (PTO-413) /Mail Date				
Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08 Paper No(s)/Mail Date		ormal Patent Application (PTO-152)				
U.S. Petent and Trademark Office PTOL-326 (Rev. 1-04) Office A	Action Summary	Part of Paper No./Mail Date 20041203				

DETAILED ACTION

Priority

1. Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

Drawings

2. The drawings are objected to as failing to comply with 37 CFR 1.84(p)(4) because reference characters "10", "11", and "12" have both been used to designate the unit cell in Figure 1A. Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Specification

3. The title of the invention is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

The following title is suggested: "Electronic Camera with Backlight Correction Capability"

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

4. Claims 3,6,9,12 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Applicant refers to the electronic shutter operation as sequentially draining charges by supplying a reset signal to a reset line from said reset row-shifter in claim 1. In claims 3,6,9, and 12, applicant claims that if a still image mode indication signal is received during an electronic shutter operation, an image signal readout operation is performed following the electronic shutter operation. Once the electronic shutter operation is finished, there are no charges in the photoelectric conversion elements to be readout. There is no utilization for this operation.

Claim Rejections - 35 USC § 103

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1,2,4,5,13,14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Juen (US # 6,542,194) in view of Yamagishi (US # 6,710,808).

As to claim 1, Juen teaches an electronic camera (see Figure 4) comprising: a MOS type solid-state image pickup device (see Figure 4, imaging element "45"; Col. 13, Lines 41-44) comprising (i) a semiconductor substrate {It is well known that MOS type image sensors are built upon a semiconductor substrate. \}, (ii) a number of photoelectric conversion elements (see Figure 8, PD 11,12, 21,22, etc.) formed in one surface of said semiconductor substrate in a matrix shape along a plurality of rows and columns (see Figure 8), (iii) a switching circuit provided for each photoelectric conversion element and electrically connected to an corresponding photoelectric conversion element (see Figure 8, transistors circuit consisting of "QTij", "QAij", and "QRSTij") each switching circuit controlling generation of an output signal representative of charges accumulated in said corresponding photoelectric conversion element and drainage of said charges (see Col. 9, Lines 25-32; Col. 14, Lines 5,6), (iv) a row selection signal line disposed for each photoelectric conversion element row (see Figure 8, line corresponding to signal "TR1") and electrically connected to corresponding switching circuits (see Figure 8), each row selection signal line being supplied with a row selection signal for controlling generation of said output signal (see Col. 10, Lines 62-65), (v) a plurality of output signal lines each of which is corresponded to at least one pixel column (see Figure 8, line "LV1,2,3,...) and on each of which

said output signal is generated (see Col. 11, Lines 21-29), vi) a reset signal line disposed for each photoelectric conversion element row and electrically connected to corresponding switching circuits (see Figure 8, line connected to the drain of transistor "QRSTij"), each reset signal line being supplied with a reset signal for controlling drainage of said charges (see Figure 8, "PRDi"; Col. 10, Lines 62-65), (vii) a readout row-shifter (see Figure 8, signal reading scanning register "62") for sequentially supplying said row selection signal to each row selection signal line (see Col. 11, Lines 58-64), (viii) a reset row-shifter (see Figure 8, reset scanning register "63") for sequentially supplying said reset signal to each reset signal line (see Col. 11, Lines 65-67, Col. 12, Lines 1-6), and (ix) an output device electrically connected to each output signal line (see Figure 8, circuit consisting of transistor "QTCsi", capacitor "CTsi") for sequentially generating and outputting image signals representative of said output signals (see Col. 11, Lines 24-27), an image signal processor for generating moving image data or still-image data based on said image signals output from said MOS type solid-state image pickup device (see Figure 4, signal processor "48", Col. 3, Lines 16-19; image display "49"), a still image indication signal generator for generating a still image indication signal for indicating image pickup of a still image (see Col. 7, Lines 61-63), a moving image mode controller (see Figure 4, CPU "52") being connected to said MOS type solid-state image pickup device for continually controlling operation of said MOS type solid-state image pickup device (see Col. 7, Lines 45-55), said moving image mode controller makes said MOS type solid-state image pickup device repeat (a) an image signal read operation of sequentially supplying said row selection signal from the readout row-shifter to a plurality of predetermined row selection signal lines for sequentially generating said output signals on each output signal line (see Col. 10, Lines 50-65) and (b) an

electronic shutter operation of sequentially supplying said reset signal from the reset row-shifter to said reset signal lines corresponding to at least said rows to be subjected to said image signal read operation for sequentially draining said charges accumulated in the photoelectric conversion elements (see Col. 5, Lines 35-37), and a correcting still image mode controller being connected to said MOS type solid-state image pickup device (see Figure 4, CPU "52") for controlling operation of said MOS type solid-state image pickup device (see Col. 7, Lines 45-55) in place of said moving image mode controller when said still image indication signal is made (see Col. 7, Lines 61-63), an exposure time of each photoelectric conversion element is set equal to or shorter than a time duration including an issuance time of a flashing device operation signal and necessary for performing two image signal read operations before and after one electronic shutter operation (see Figure 2A, exposure time "Tex", {As seen from the timing diagram, one signal reading period is longer than the exposure time, let alone two, and any other time duration signal, namely a flashing device operation signal combined with the time of two signal readout operations will be longer than the exposure time.}, and after a lapse of said exposure time, said correcting still image mode controller makes said MOS type solid-state image pickup device perform an image signal read operation of sequentially supplying said row selection signal from the readout row-shifter to each row selection signal line for sequentially generating said output signals on each output signal line (see Figure 2A, {The signal readout is performed after the exposure time, Tex. \}). The claim differs from Juen in that it requires that a flashing device for emitting a flash in reception to a predetermined signal be included in the electronic camera, and that the signal is made in a state where the readout row shifter and the reset row shifter are not operated.

In the same field of endeavor, Yamagishi teaches an electronic camera (see Figure 1) which contains a flashing device for emitting a flash (see Figure 1, electronic flash portion "48", Col. 5, Lines 14-16) in response to the reception of a predetermined signal (see Figure 1, Col. 7, Line 4, {Signal comes from the flash setup button, goes to the system control circuit and outputs a signal to the electronic flash portion.}), and that the signal is made at a state where the readout row shifter and the reset row shifter are not operated (see Figure 7 and 8, {The flash signal (S307) is made at a point when the CCD, or CMOS (see Col. 3, Line 51) has already been cleared (S303) and the signal readout hasn't happened yet (S315).}). In light of the teaching of Yamagishi, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the electronic camera of Juen to include a flashing device where a flash is emitted in response to the reception of a predetermined signal and the predetermined signal is made at a point where the readout row shifter and the reset row shifter are not operated. Such a modification would allow for an object to be captured to be more illuminated, so an image of said object can be faithfully presented, and having the readout row shifter and the reset row shifter inoperable during the flash signal, allows for constant framing intervals of image sensing (see Yamagishi, Col. 2, Lines 53-55) that prevent sensing images of uneven quality.

As to claim 2, Juen, as modified by Yamagishi, teaches an electronic camera according to claim 1 (see 103(a) rejection above), wherein the image signal read operation by said moving image mode controller and the image signal read operation by said correcting still image mode controller include (i) operation of sequentially supplying said row selection signal from the readout row-shifter to a plurality of predetermined row selection signal lines for sequentially generating said output signals on each output signal line in the unit of a photoelectric conversion

element row (see Juen, Col. 10, Lines 50-65) and (ii) operation of sequentially draining said charges accumulated in each photoelectric conversion element from which said output signal was generated, in the unit of a photoelectric conversion element row (see Juen, Col. 10, Lines 65-67, Col. 11, Lines 1-6).

As to claim 4, Juen, as modified by Yamagishi, teaches an electronic camera according to claim 1 (see 103(a) rejection above), further comprising: a non-correcting still image mode controller being connected to said MOS type solid-state image pickup device (see Figure 4, CPU "52") for controlling operation of said MOS type solid-state image pickup device (see Col. 7, Lines 45-55) in place of said moving image mode controller when said still image signal is made, wherein without making said flashing device operation signal (see Figure 7, "S307"), said non-correcting still image mode controller makes said MOS type solid-state image pickup device perform an image signal read operation of sequentially supplying said row selection signal from the readout row-shifter to each row selection signal line for sequentially generating said output signals on each output signal line (see claim 2 rejection above; see Yamagishi, Figure 8, "S315"); and still image mode designating device for specifying beforehand a still image mode controller to be operated when said still image indication signal is made (see Col. 7, Lines 61-63, {Designating device is the button.}).

As to claim 5, the limitations in claim 5 can be found in claim 2. Therefore, claim 5 is analyzed and rejected as previously discussed with respect to claim 2.

As to claim 13, Juen, as modified by Yamagishi, teaches an electronic camera according to claim 1 (see 103(a) rejection above), further comprising: an auto iris for adjusting an amount of light incident upon said MOS type solid-state image pickup device (see Juen, Figure 1,

mechanical focal plane shutter "1"), wherein said correcting still image mode controller in operation further performs an exposure amount adjustment operation of adjusting said auto iris to reduce a difference between exposure amounts to be caused by a difference between an exposure time under a control of said correcting still image mode controller and an exposure time under a control of said moving image mode controller (see Juen, Col. 9, Lines 11-24).

As to claim 14, the limitations in claim 14 can be found in claim 13. Therefore, claim 14 is analyzed and rejected as previously discussed with respect to claim 13.

As to claim 17, Yamagishi teaches a digital output device that receives said analog signals, converts the analog signals into digital signals, and outputs the digital signals (see Figure 1, A/D Converter "16").

As to claim 18, the limitations of claim 18 can be found in claim 17. Therefore claim 18 is analyzed and rejected as previously discussed with respect to claim 17.

Allowable Subject Matter

8. Claims 7,8,10,11,15,16,19,20 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

The following is a statement of reasons for the indication of allowable subject matter: As to claim 7, the prior art does not teach or fairly suggest a still image mode controller being connected to a MOS type solid-state pickup device for controlling operation of the MOS type solid-state image pickup device, wherein an exposure time of each photoelectric conversion element is set longer than a time duration including an issuance time of a flashing device

Application/Control Number: 09/837,517 Page 10

Art Unit: 2615

operation signal and necessary for performing two image signal operations before and after one electronic shutter operation. As to claims **8,10,11,15,16,19,20**, claims **8,10,11,15,16,19**, and 20 are objected to as being dependent upon the objected claim 7.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Anthony J. Daniels whose telephone number is (703) 305-4807. The examiner can normally be reached on 8:00 A.M. - 4:30 P.M..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Andy Christensen can be reached on (703) 308-9644. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

12/06/2004

PRIMARY EXAMINER